



Material Safety Data Sheet

Date prepared: June 23, 2006

Section 1 - Product and Company Information

Product Name: Decal Works Step 1 Adhesive Remover
Product Purpose: Aids in removal of vinyl labels and decals without harm to paint.
Manufacturer: Rapid Tac, 186 Combs Drive, Merlin, OR 97532, USA

Phone: 1-800-350-7751 International: 703-527-3887 (collect)

Emergency Telephone Number: 1-800-424-9300

Note: The purpose of this MSDS is to provide safe handling, shipping and disposal information for users of the product. It is not intended to, nor does it, provide complete or extensive toxicological data on the product or its components.

Section 2 - Composition & Information on Ingredients

Table with 6 columns: CAS #, SARA 313, Material or Component, %, RQ#, Exposure Limits (TWA, STEL). Rows include Petroleum distillate and d-limonene.

Contains non-hazardous surfactants which may affect eye and skin irritation properties. No component is listed in "Threshold Limit Values and Biological Exposure Indices for 2006" from ACGIH except as noted above.

Section 3 - Hazards Identification

Emergency overview:

Mild solvent fluid. Harmful if swallowed. Eye irritant. May irritate skin on extended or repeated exposure. Keep from sparks, flame and all sources of ignition.

For additional information on toxicity, please refer to Section 11.

Reference 49CFR 171.8 173, OSHA 29CFR 1910.1200 and SARA 302, 311, 312, and 313.

Table with 5 columns: Hazard Health Categories, Health, Fire, Pressure, Reactivity. Rows for Immediate and Delayed.

HMIS Hazard Rating: Health 1, Fire 2, Instability 0, Other NA
NFPA Hazard Rating: Health 1, Flammability 2, Reactivity 0, Special NA

Notice: HMIS and NFPA ratings involve the subjective evaluation of the hazardous aspects of the individual product components and can vary between preparers.

Section 4 - First Aid Measures

Oral: If swallowed, wash out mouth with water provided person is conscious. Do not induce vomiting.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration. If breathing is difficult administer oxygen.

Skin Contact: In case of contact, wash skin with soap and water.

Eye Contact: Contamination of the eyes should be treated by immediate and prolonged irrigation with copious amounts of water.

Section 5 - Fire Fighting Measures

Explosion hazard:

Product offers an explosion hazard if misted into the air or heated above its flash point of 120 deg. F.

Ignition Data:

Dust Potential: None
Flash Point: 120 degrees F
Auto-Ignition Temperature: Not determined
Flammable Limits: Not determined



Fire Fighting Equipment: Foam or dry chemical. Water mist will disperse and cool the product. Do not use a strong stream of water as this can spread the fire.

Specific or Exceptional Hazards: None

Section 6 -Accidental Release Measures

Procedure to be followed in case of leak or spill:

Procedures or personal precautions:

Remove unnecessary personnel from the spill area. Avoid contact or inhalation. Protect from all ignition sources.

Methods for cleaning up:

Absorb on dry vermiculite, etc. for disposal as a solid waste.

Land spill and toxic releases:

Advise all appropriate regulatory agencies in whose jurisdiction you are located for discharges in excess of the appropriate threshold amounts. Reference Sec 313 chemicals listed in Sec 2, and the exemptions from reporting requirements listed by EPA for reporting EPCRA releases. Example exemptions are: "If you otherwise use any of the listed toxic chemicals (without incorporating it into any product or producing it at a facility), the threshold quantity is: 10,000 pounds per toxic chemical or category over the calendar year."

Other exemptions apply to materials below de minimis concentrations, and those used "in routine janitorial or facility grounds maintenance", or "In motor vehicle maintenance (including motor fuel)."

The above information is subject to change. For current exemptions you may call EPCRA Information Hotline at 800-535-0202 or 703-412-9877.

Section 7 -Handling and Storage

Handling:

Avoid extended contact and inhalation. Flush or wash off immediately after contact.

Storage:

Keep container closed. Store in a cool dry place. Protect from oxidizing agents and all sources of ignition.

Section 8 -Exposure Controls and Personal Protection

Engineering controls:

Use mechanical ventilation is required to meet exposure limits. Use standard industrial good practices.

Personal protective equipment:

Respiratory:

None

Hand/skin:

Rubber gloves

Eye:

Safety goggles

General hygiene measures:

Wash thoroughly after handling. Wash contaminated clothing before reuse.

Section 9 - Physical and Chemical Properties

Property	Value	Property	Value
Appearance and form:	Clear colorless liquid		
Odor:	Citrus solvent		
Specific Gravity:	< 1	Flash point °F:	120
pH	Not applicable	Flash point °C:	48
% Phosphorous	None	Vapor pressure @20 °C, mm Hg	Not determined
VOC content:	96%	Freezing point °C:	Not determined
Solubility in hydrocarbon:	Complete	Solubility in water:	Disperses
Melting point:	N/A	Viscosity:	N/A



Decal Works: Step 1 Adhesive Remover

Page 3

California Rule 102 (66): Contains no photochemically active materials which produce smog or ozone at ground level.

Section 10 - Stability and Reactivity

Incompatible materials and conditions to avoid:

Oxidizing agents. Avoid exposure to flames, sparks and all sources of ignition.

Hazardous decomposition products:

Burns with heavy black smoke.

Section 11 - Toxicological Information

Route of exposure:

Skin absorption:

Absorption through the skin is not known to be likely nor deleterious.

Inhalation:

Inhalation of mists may result in irritation of the breathing passages.

Ingestion:

Discomfort may result from ingestion.

Signs and symptoms of exposure:

Over exposure to vapors or fumes may cause dizziness, nausea or death by asphyxiation.

Toxicity Data on product: No data available.

No component of this product above de minimis limits has known carcinogenic, or reproductive effects except as stated in Section 2 above.

Section 12 - Ecological Information

None available on this product.

Section 13 - Disposal Considerations

Appropriate method of disposal of substance:

Absorb all spill material onto non-combustible absorbent for disposal.

Observe all federal, state and local environmental discharge regulations.

Section 14 - Transport Information

DOT Proper Shipping Name, Hazard Class, UN or NA Number, Packing Group, Emergency Response Guide:

Paint related material, 3, UN1263, PG III (Contains petroleum distillates)

Flammable, Limited quantity per 173.150(b)(3) 1.3 gallons in 66# gross wt. Package. ERG 127

Passenger aircraft or rail 60 liters; Cargo aircraft 220 liters

IATA: Proper Shipping Name:

Flammable liquid, n.o.s., PG III, ERG Code 3L

Section 15 - Regulatory Information

SARA 313:

See Section 2 for complete listing of Sec 313 items, if any.

TSCA (Toxic Substance Control Act):

All ingredients are listed on the TSCA Chemical Inventory.

California Prop. 65:

None

Section 16 - Additional Information and Disclaimer

For disposal purposes product as made has the characteristic of ignitability, like "Unlisted Hazardous Waste D001", RQ 100#. Information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. Since conditions of use are beyond our control we make no warranties, expressed or implied as to safety or appropriateness of the product for any use or condition.